

Simple, Powerful and Optimised for video



ST350 EnterpriseStorage EX900 StorageExpander

Features

PREDICTABLE PERFORMANCE

A powerful appliance designed for video storage, featuring the latest generation of our advanced, award-winning StorStac™ Storage Area Network (SAN) software and a feature-rich GUI.

Management and monitoring of your video surveillance infrastructure just got easier.

NO FRAME LOSS

Our unique VSOP Video Stream Optimisation technology delivers smooth video recording and playback. It eliminates disk fragmentation and frame loss to ensure continuous long-term write performance.

OPEN PLATFORM

Designed to work with all major OS and Video Management Software for optimal recording.

PERFORMANCE MONITORING

Manage and track video assets for one or more sites and receive actionable information about the video network infrastructure. Continuous diagnostics including alerts, advisories, and daily status reports of server, storage, switches, camera and infrastructure disruptions help prevent issues and ensure maximum uptime.

SURVEILLANCE/ ENTERPRISE DRIVES

Designed for video storage to deliver reliable 24×7 operation—optimised for low power consumption, quiet operation, smooth video streaming, enterprise-class reliability and high capacity. Ensuring highest performance, and significant cost savings.

- Ultra-high performance storage with comprehensive CCTV infrastructure performance monitoring
- Fully scalable and supports a large number of ultra-high definition cameras
- Maintains image quality without frame loss
- Award-winning technologies

Simply Smarter

The EnterpriseStorage ST350 rackmount works seamlessly with the EnterpriseServer (SE) and ServerBlade (SB) appliances to deliver a total storage solution. VMS software operates on the SE and SB products while video data is stored on the EnterpriseStorage and up to three Expanders. Each EX900 StorageExpander holds an additional 12 drives of up to 10TB each. The result is an extremely high capacity, ultra-high performance video surveillance storage and server solution.

Faster & More Powerful

The ST350 combines the single high-performance Intel® Xeon® E5-2603 v4 quad-core processor with up to 3.0 GHz clock speed and 16GB DDR4 2133 MHz ECC memory. Its high bandwidth connectivity and unmatched LAN connectivity with 2 GbE ports, gives it the speed and responsiveness for the unique performance requirements of video surveillance infrastructure.

Tested & Certified

The Intransa Technology Labs continually test and certify cameras, VMS systems, NVRs and other applications for use with Intransa SE (EnterpriseServer) and SB (ServerBlade). Used in conjuction with the ST350, they are specifically designed for physical security's real-world demanding requirements.

Fully Protected

We provide advanced RAID technologies which eliminate disk drive failure - the number one cause of lost video and downtime. Disk drives are hot swappable without interruption in service or loss of data. The second most common failure is power supplies. The ST350 eliminates this by providing dual redundant power supplies. The ST350 only uses ECC RAM and video being stored and transferred within the system is protected.

Flexible & Scalable

Choose from versions with up to 48TB of storage and two SSD drives for the OS in RAID 1 configuration. The ST350 combines storage capacity with exceptional performance to deliver simple, reliable video storage to suit your needs. Expand the ST350 with the EX900 StorageExpander, allowing capacity to grow by an additional 480TB.



Simple,
Powerful and
Optimised for video

Features

Specifications

QUICK TO INSTALL

The EnterpriseStorage can be installed in just a few minutes as all the integration work and testing has already been done. It just needs to be plugged in and configured to your project needs.

Intransa Systems Inc.

US Toll Free: (855) 546 8726

(855) 5INTRANSA

US Tel: +1 (650) 713 2065 UAE Tel: +971 4 330 0433

General Information: info@intransa.com

Sales: sales@intransa.com Support: support@intransa.com Website: www.intransa.com

Copyright © 2017 Intransa Systems Inc. Specifications are subject to change without notice. Intransa and the Intransa logo are trademarks of Intransa Systems Inc.

VideoAppliance is a trademark of Intransa Systems Inc.

All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.

Core Technology

Models ST350 Storage controller EX900 Storage expander

CPU Type Intel® Xeon® E5-2603 v4
Controllers Single or Dual
Memory size 8GB per controller

Memory type DDR4 2133 ECC UDIMM
Cache Type Mirrored/Persistent

Cache Settings Cache can be configured to write-back, write-through or

mirrored **for each virtual disk volume

Max. HDDs 48
Host Connect Options IPSAN

Interface Ports 2x GbE iSCSI ports (per Ctrl.)

One 24Gbps downstream SAS 2.0 ports (per Ctrl.)

One Serial port (per Ctrl.) Two USB 3.0 ports (per Ctrl.)

HDD Type Video Class SATAIII

Drives 3.5", 24/7/365. Video Class SATAIII - 4, 5, 6, 8 & 10TB

Redundancy Power Supplies

Fans

Availability Features IP & disk group failover**

Auto drive rebuild w/global spares

Serviceability Power Supplies

Fans

System Software

Data Protection RAID 0, 1, 5, 50, 10, 6, 60
Disk Group concatenation
Bad sector reconstruction

Bad sector reconstruction Scheduled drive inspection SMART diagnostics

Management Web-based management utility

Telnet

Serial console management

SNMP management (Enterprise MIB)

ISNS

Security LUN masking, Chap authentication

Software Services Online capacity expansion

Online software upgrades (OS/JBOD/Drives)
Volume management (256 LUNs), Smart Sparing

Intelligent Power Management

Physical Characteristics

ST350

Dimensions (in./cm)
Weight (w/HDDs)

28.4kg (62.5 Lbs)

EX900

Dimensions (in./cm)
Weight (w/HDDs)

3.4" x 17.6" x 23.7" / 8.68 x 44.58 x 60.12 cm

3.4" x 17.6" x 23.7" / 8.68 x 44.58 x 60.12 cm

28.4kg (60.5 Lbs)

Power 920W Redundant Platinum power supply

Operating Environment

onment 10-35°C (50-104°F) 10%-90% non-condensing

Designed for 24x7x365 Operation

Compatibility Windows and Linux

^{*}Performance derived from an Intransa Video Surveillance configuration (test data available on request)

^{**}Dual models only