

Simple, Powerful and Optimised for video



VA424 VideoAppliance

Features

PREDICTABLE PERFORMANCE

A powerful appliance with a finely-tuned OS, designed for video processing and recording. Award-winning technologies include VSOP Video Stream Optimisation delivering smooth video recording and playback. This eliminates disk fragmentation and the resulting frame loss for continuous write performance.

OPEN PLATFORM

All major OS and Video Management Software can be easily integrated and pre-loaded, having been pre-tested and qualified.

CHOOSE YOUR SOFTWARE

Your preferred video analytics software can be pre-loaded and ready to run at installation. These include facial recognition, abnormal behaviour detection, suspect tracking, mobile information and incident management, cybersecurity and more, to further empower your solution.

PERFORMANCE MONITORING

Manage and track video assets for one or more sites and receive actionable information about the video network infrastructure. Continuous diagnostics including alerts, advisories, and daily status reports of server, storage, switches, camera and infrastructure disruptions help prevent issues and ensure maximum uptime.

- Ultra-high performance with onboard software analytics
- Fully scalable and supports a large number of high definition cameras
- Maintains image quality without frame loss
- Award-winning technologies

Simply Smarter

The VideoAppliance VA424 rackmount integrates VMS (Video Management Software) and storage into a simple to use, ultra-high performance video surveillance storage server solution. This eliminates the cost of a separate VMS server, significantly reduces cabling and the complexity of integrating VMS, OS, commodity server and storage, while significantly lowering the total cost of ownership.

Tested & Certified

The Intransa Technology Labs constantly test and certify cameras, VMS systems, NVRs and other applications for use with Intransa products for physical security's real-world demanding requirements. This allows for risk-free integration, without the complications of products that are not designed for physical security.

Faster & More Powerful

The VA424 combines the dual high-performance Intel® Xeon® E5-2603 v4 six-core processors with up to 1.7G GHz clock speed and 16GB DDR4 2400 MHz ECC memory. Its high bandwidth connectivity and unmatched LAN connectivity with 4 GbE ports and an option of dual 10GbE ports, gives it the speed and responsiveness for the unique performance requirements of video surveillance infrastructure.

Fully Protected

We provide advanced RAID technologies which eliminate disk drive failure - the number one cause of lost video and downtime. Disk drives are hot swappable without interruption in service or loss of data. The second most common failure is power supplies. The VA424 eliminates this by providing dual redundant power supplies. The VA424 only uses ECC RAM and video being stored and transferred within the system is protected.

Flexible & Scalable

Choose from a server only or versions with up to 48TB of storage and two SSD drives for the OS in RAID 1 configuration. The VA424 combines storage capacity with exceptional performance to deliver simple, reliable video storage to suit your needs. Expand the VA424 with the ST350, allowing capacity to grow by an additional 480TB.



Simple,
Powerful and
Optimised for video

Features

Specifications

SURVEILLANCE DRIVES

Surveillance drives are designed for video storage to deliver reliable 24×7 operation — optimised for low power consumption, quiet operation, smooth video streaming, enterprise-class reliability and high capacity. Ensuring highest performance, and significant cost savings.

QUICK TO INSTALL

The VA424 can be installed in just a few minutes as all the integration work and testing has already been done. It just needs to be plugged in and configured to your project needs.

Intransa Systems Inc.

US Toll Free: (855) 546 8726

(855) 5INTRANSA **US Tel:** +1 (650) 713 2065 **UAE Tel:** +971 4 330 0433

General Information: info@intransa.com

Sales: sales@intransa.com
Support: support@intransa.com
Website: www.intransa.com

Copyright © 2017 Intransa Systems Inc. Specifications are subject to change without notice. Intransa and the Intransa logo are trademarks of Intransa Systems Inc.

VideoAppliance is a trademark of Intransa Systems Inc.

All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.

Core Technology CPU Type

CPU Type Dual Intel® Xeon E5-2603 v4 Broadwell 1.7 GHz
Socket 2 x Socket 2011 v3
Core Logic Intel® C612 Chipset
Benchmark/Clock speed 8807 / 1.7GHz

Memory size 16GB (2x8GB)
Memory type DDR4 2400 ECC

Video Storage Performance Up to 160Mbps / 20MBs internal

Expansion

Expansion Slot

Slot Type 1 x PCI-E x16

Storage

HDD Bays 4x Hot-swap 3.5" and 2x 2.5"

Drive support 4, 6, 8 & 10TB SATA III Video Class
120GB SSD

RAID 0, 1 and 5

Ethernet

Data 4 x GbE (Intel® i210) or 2 x 10GbE Intel® X540

Management 1 x GbE (i210)

Video

Onboard Graphic ASPEED AST2400

On Board I/O

2 x USB 3.0 (front) and 2 x USB 3.0 (rear)

1 x D-Sub (1x rear) 1 x Serial Port (COM1)

Management Solution Remote IPMI support

Compliance

Safety US/Canada (UL1950-CSA950)

Europe (CE, EN55022 compliance to EU Directive 89/366/EEC & TUV) US (FCC, CFR47 Part 15, Class A) Europe (CE, EN55022 class A & EN55024)

Physical Characteristics

Server dimensions (in./mm) 24" x 19" x 1.75" / 625 x 482.6 x 44.4 mm

Server weight 32.6lbs / 14.8kg Shipping weight 39.2lbs / 17.8kg

Box dimensions 32.5" x 23.5" x 6" / 825.5 x 597 x 152 mm

Power

EMI

Voltage 100 - 240 VAC
Watts 750W 80 PLUS Platinum

Operating Environment

Operation temperature
Non-operation temperature

Humidity
Operating altitude

Designed for 24x7x365 Operation

10°C to 35°C -40°C to 70°C

Dual redundant 1+1

20% to 90% (non-condensing) 0 to 10,000ft / 0 to 3000m



