



**Simple,
Powerful and
Optimised for video**



VA625 VideoAppliance

Features

PREDICTABLE PERFORMANCE

A powerful appliance with a finely-tuned OS, designed for video processing and recording. Award-winning technologies include VSOP Video Stream Optimisation delivering smooth video recording and playback. This eliminates disk fragmentation and the resulting frame loss for continuous write performance.

OPEN PLATFORM

All major OS and Video Management Software can be easily integrated and pre-loaded, having been pre-tested and qualified.

CHOOSE YOUR SOFTWARE

Your preferred video analytics software can be pre-loaded and ready to run at installation. These include facial recognition, abnormal behaviour detection, suspect tracking, mobile information and incident management, cybersecurity and more, to further empower your solution.

PERFORMANCE MONITORING

Manage and track video assets for one or more sites and receive actionable information about the video network infrastructure. Continuous diagnostics including alerts, advisories, and daily status reports of server, storage, switches, camera and infrastructure disruptions help prevent issues and ensure maximum uptime.

- Ultra-high performance with onboard software analytics
- Fully scalable and supports a large number of high definition cameras
- Maintains image quality without frame loss
- Award-winning technologies

Simply Smarter

The VideoAppliance VA625 rackmount integrates VMS (Video Management Software) and storage into a simple to use, ultra-high performance video surveillance storage server solution. This eliminates the cost of a separate VMS server, significantly reduces cabling and the complexity of integrating VMS, OS, commodity server and storage, while significantly lowering the total cost of ownership.

Tested & Certified

The Intrinsa Technology Labs continually test and certify cameras, VMS systems, NVRs and other applications for use with Intrinsa products for physical security's real-world demanding requirements. This allows for risk-free integration, without the complications of products that are not designed for physical security.

Faster & More Powerful

The VA625 combines single high-performance Intel® Xeon® E5-2620 v4 eight-core processors with up to 3.0GHz clock speed and 16GB DDR4 2400 MHz ECC memory. Its high bandwidth connectivity and unmatched LAN connectivity with 4 GbE ports or the option of dual 10 GbE ports, gives it the speed and responsiveness for the unique performance requirements of video surveillance infrastructure.

Fully Protected

We provide advanced RAID technologies which eliminate disk drive failure - the number one cause of lost video and downtime. Disk drives are hot swappable without interruption in service or loss of data. The second most common failure is power supplies. The VA625 eliminates this by providing dual redundant power supplies. The VA625 only uses ECC RAM and video being stored and transferred within the system is fully protected.

Flexible & Scalable

Choose from a server only or versions with up to 144TB of storage and two SSD drives for the OS in RAID 1 configuration. The VA625 combines storage capacity with exceptional performance to deliver simple, reliable video storage to suit your needs. Expand the VA625 with Expander series or with the ST350, allowing capacity to grow by an additional 480TB.

Features

SURVEILLANCE DRIVES

Surveillance drives are designed for video storage to deliver reliable 24x7 operation — optimised for low power consumption, quiet operation, smooth video streaming, enterprise-class reliability and high capacity. Ensuring highest performance, and significant cost savings.

QUICK TO INSTALL

The VA625 can be installed in just a few minutes as all the integration work and testing has already been done. It just needs to be plugged in and configured to your project needs.

Intransa Systems Inc.

US Toll Free: (855) 546 8726

(855) 5INTRANSA

US Tel: +1 (650) 713 2065

UAE Tel: +971 4 330 0433

General Information: info@intransa.com

Sales: sales@intransa.com

Support: support@intransa.com

Website: www.intransa.com

Copyright © 2017 Intransa Systems Inc.

Specifications are subject to change without notice.

Intransa and the Intransa logo are trademarks of Intransa Systems Inc.

VideoAppliance is a trademark of Intransa Systems Inc.

All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.

Specifications

Core Technology

CPU Type	Single Intel® Xeon E5-2620 v4 Broadwell (2.1-3.0 Ghz)
Socket	2 x Socket 2011-3
Core Logic	Intel® C612 Chipset
Benchmark/Clock speed	11358 / 2.1 GHZ
Memory size	16GB (2x8GB)
Memory type	DDR4 2400 ECC
Video Storage Performance	Up to 160Mbps / 20MBs internal

Expansion

Expansion Slot	5 (Low Profile)
Slot Type	3 x PCI-E 3.0 x 16 2 x PCI-E 3.0 x 8

Storage

HDD Bays	12x Hot-swap 3.5" and 2x 2.5"
Drive support	4, 6, 8 & 10TB SATA III Video Class / 120 GB SSD
RAID levels	0, 1, 5 and 6

Ethernet

Data	4 x GbE (Intel® i210) or 2x 10GbE Intel® X540
Management	1 x GbE (Intel® i210)

Video

Onboard Graphic	ASPEED AST2400
Optional HD Graphic	GT1030 2GB DDR5
Benchmark performance	2287

On Board I/O

	2 x USB 3.0 (front) and 2 x USB 3.0 (rear)
	1 x D-Sub (1x rear)
	1 x Serial Port (rear)
With Optional HD Graphic	1 x Dual-Link DVI-D and 1 x HDMI 2.0b
Management Solution	Remote IPMI support

Compliance

Safety	US/Canada (UL1950-CSA950) Europe (CE, EN55022 compliance to EU Directive 89/366/EEC & TUV)
EMI	US (FCC, CFR47 Part 15, Class A) Europe (CE, EN55022 class A & EN55024)

Physical Characteristics

Server dimensions (in./mm)	24" x 19" x 3.5" / 625 x 482.6 x 87 mm
Server weight	52lbs / 23.6kg
Shipping weight	58.6lbs / 26.6kg
Box dimensions	32.5" x 23.5" x 7.5" / 825.5 x 597 x 190.5 mm

Power

Voltage	Dual redundant 1+1
Watts	100 - 240 VAC 875 W 80 PLUS

Operating Environment

Operation temperature	Designed for 24x7x365 Operation 10°C to 35°C
Non-operation temperature	-40°C to 70°C
Humidity	20% to 90% (non-condensing)
Operating altitude	0 to 10,000ft / 0 to 3000m

